

## Automatic Strapping Machine

### Features

- Modular designed Aluminum alloy arch, easy to assemble and disassemble.
- Outside Tension Adjustment: it is easy to adjust the tension via Tension Knob.
- Automatic positioning and re-try functions: to secure the strap goes to its' proper position and every cycle is accurate and efficient.
- Controlled by P.C. Board with multiple functions.
- Convenient operating modes with panel, ball switch and foot pedal switch.
- ABS Dispenser.
- With CKD frame and powder painting on frame.
- Internal electricity is 24V accessing, prevent operators from shocking.
- Casters wheel for moving on factory floor.

### Specifications

Model	JN 85E
Arch Size	850W x 600H mm
Tension	Max. 70 Kgs
Table Height	805 mm
Strap Width	6-15 mm
Sealing Method	Heat Sealing
Power Supply	220/380V 50/60 Hz, 3Ph
Dimensions	1400(L)x640(W)x 1475(H)
Weight	220 Kgs



Regd Office: A-34, Ashok Nagar, Street No. 4, Mandoli Road, Shahdara, Delhi – 110093

Mktg Office: B-169, Ashok Nagar, Street No 6, Shahdara, Delhi - 110093

Ph: 9953471435, 9350471435, 9250557066

E-mail: info@dipackcorporation.in, dipack.corp@gmail.com

[www.dipackcorporation.in](http://www.dipackcorporation.in)